

CERTIFICATE OF QUALITY

Laško, 01.10.2012



| | | |
|---------------------------|--|-----------------------------|
| Producer | DEMIT d.o.o., Spodnja Rečica 77, SI - 3270 Laško | |
| Technical name | Energy saving paint THERMOSUN | |
| Purpose | Energy saving paint THERMOSUN is used for interior wall and ceiling painting. | |
| Properties | Because of its thermal insulating and reflexive characteristics it provides considerable energy savings. It prevents the condensation of moisture on the walls and abolishes so the main reason for the occurrence of algae and mildew. | |
| Ingredients | Organic binder dispersion, hallow glass bubbles, mineral fillers, water, cellulose thickening agents and additives. | |
| Quality control | Raw materials and end product is controled in internal laboratory. | |
| Phisical data | Density (ρ) | ca. 0,85 kg/dm ³ |
| | Water vapour permeability (μ) | ca. 140 |
| | Sd (d = 0,2 mm) | ca. 0,024 m |
| | Dry substance content | ca. 64% |
| | Broken glass bubbles | max. 5% |
| Testing of product | Institute of public health Maribor, Number of reoport 53132 | |
| Safety data sheet | According to the criteria of the Regulation on the classification, packaging and labeling of dangerous preparations, harmonized with the EU Directive 1999/45/EC, the product is not classified as hazardous. | |

2  d.o.o.
Spodnja Rečica 77, SI-3270 Laško

Srebot Oto
Research-Technology & Quality Manager

